

C5000 Series Door Closer

Applications, Features, & Covers, Arms, and Plates

APPLICATIONS:

Suitable for light to moderate-traffic doors found in apartments and retail complexes, offices, condominiums, restaurants, and retirement communities. This economical closer retrofits into many popular hole patterns and includes standard features such as: sex nuts and bolts, tri-packed arms, and backcheck. Available in aluminum and duranodic finishes, and two adjustable sizes (1-4, 3-6).



FEATURES:

CERTIFICATIONS: ANSI A156.4, Grade 1, UL Listed, ISO 9001 certified. Meets ADA requirements when adjusted to size 1.



MECHANISM: Rack-and-pinion mechanism contained in a cast aluminum housing

SIZES: Available in two adjustable sizes: 3-6 and 1-4

FINISHES: 689 Sprayed Aluminum
695 Duranodic

HANDED: Non-handed for standard, top-jamb, and parallel arm installations (tri-packed)

BOLTS: Sex nuts and bolts standard (wood/machine screw packs also included)

ARMS: Hold-open arm optional (cannot be used on fire-rated openings)

COVERS: Aluminum and duranodic plastic covers optional

ADJUSTING: Sweeping and latching speeds are controlled by separate, adjustable regulating valves to provide consistent closing speed.
Adjustable backcheck standard.

CASE QUANTITY: 10

WARRANTY: 5-year warranty

COVERS, ARMS, AND PLATES:

5000-C	Cover for the 5000 Series closer
5000-H	Friction hold-open arm for the 5000 Series closer
5000-MH	Mechanical hold-open arm with turn and stop for the 5000 Series closer
5000-DP	Drop plate for the 5000 Series closer

GENERAL LOCK

Quality & Value™

— Product Guide 103.1 — D:15