

C9000 Series Door Closer

Applications and Features

APPLICATIONS:

Suitable for high-traffic doors in office buildings, hospitals, schools, hotels, restaurants, nursing homes, apartments, and retail complexes. The 9000 Series surface closer has a heavy-duty cast iron body and forged steel arms, and is ideal for institutional and other heavy-use applications. The C9016 offers a high-quality alternative to other cast iron closers, comes in two finishes, and optional drop plates allow for installation in any situation. The C9016 comes with a 25-year warranty, one of the best in the industry. The C9016 is your best choice for high-traffic areas where rugged durability is the solution for superior door control.



FEATURES:

CERTIFICATIONS: ANSI A156.4, Grade 1, UL Listed, ISO 9001 certified. Meets ADA requirements when adjusted to size 1.



SIZES: Available in one adjustable size: 1-6

FINISHES: 689 Sprayed Aluminum
695 Duranodic

HANDED: Non-handed for standard, top-jamb, and parallel arm installations

BOLTS: Shipped with closer body, full cover, slider-type arm, parallel arm bracket, wood screws and machine screws, and sex nuts and bolts

ARMS: Hold-open arm optional (cannot be used on fire-rated openings)

COVERS: Full cover standard

DROP PLATE: Optional drop plates available for conditions where the top rail or head frame face is too narrow (see pages D:16, & D:17 for more info)

ADJUSTING: Sweeping and latching speeds are controlled by separate, adjustable regulating valves to provide consistent closing speed. Adjustable backcheck standard.

CASE QUANTITY: 6

WARRANTY: 25-year warranty

ARMS AND PLATES:

9016-H	Friction hold-open arm for the 9000 Series closer
9016-DP	Drop plate for the 9000 Series closer
9016-MH	Mechanical hold - open arm with turn and stop for the 9000 series closer
9016-S	Arm with stop for 9000 series closer
9016-DP PA	Parallel arm drop plate for 9000 series closer
9016-DP TG	Top jamb drop plate for 9000 series closer
9016-DP G	"G" drop plate for 9000 series closer

GENERAL LOCK

Quality & Value™

— Product Guide 103.1 — D:1