

Grade 2 Cylindrical Lever / Knob Locksets

K2 and L2 Series - Applications, Features, and Functions

APPLICATIONS:

Heavy-duty commercial lockset suitable for interior and exterior doors of schools, universities, medical and office buildings, hotel / motel, public buildings, and religious, multi-family, retail, and government facilities.



FEATURES:

CERTIFICATIONS: ANSI A156.2, Series 4000 Grade 2
UL Listed for all functions up to 3 hours;
meets ADA and Title 19 California Fire Marshal
requirements



MECHANISM: Cold-rolled steel chassis housing, reversible and non-handed, lever available in clutched (L) or rigid (LX), with separate lever spring mechanism to prevent sagging and droop

FINISHES: Levers: 605, 613, 626
Knobs: 605, 613, 630

DOOR THICKNESS: 1-3/8" - 1-3/4"

LATCH: 1-1/8" x 2-1/4" square-corner face plate, square 2-3/4" backset standard and 2-3/8" optional, 1/2" throw, dead-locking latch with all keyed functions, UL Listed, 3-hour fire-rated latch bolt on all locks. Radius (234 R and 238 R) and drive-in (234 D and 238 D) latches optional. Drive-in latch not UL Listed.

BACKSET: 2-3/4"

STRIKE: 1-1/4" x 4-7/8" ANSI strike standard, T-Strikes and full-lip (TS or FLS) strikes optional

THROUGH-BOLTS: Standard cylinder lever lock chassis secured to door with optional through-bolts. IC prep lever lock chassis secured with fixed through-bolts. Without through-bolts, the lock is NOT Grade 2 compliant.

KEYS: 2 cut keys

CYLINDER: Drilled 6, pinned 6 solid brass cylinder with SCH C keyway standard, accepts converter cylinder

IC CORE: Prepped for either 6-pin (with spacer) or 7-pin small format interchangeable core. (Less core; cylinders are purchased separately)

IC CORE KNOBS: Entry and Storeroom functions only; available in 626 finish only. (Less core; cylinders are purchased separately. IC knob "B" design only).

TRIM: Rose on both lever and knob locks is 3-5/16" in diameter. Lever style is "S" style and lever return is 3/8" from the door. Knob styles are "P" style and "B" style.

CASE QUANTITY: 6

WARRANTY: 25-year mechanical warranty and 5-year finish warranty

FUNCTIONS:



PASSAGE - L210 / K210 - (ANSI F75)
Latch bolt by levers at all times.



CLUTCHED PRIVACY - L240 / K240 - (ANSI F76)
Latch bolt by levers. Outside lever locked by pushbutton in inside lever. Rotating inside lever or closing door releases pushbutton. Emergency release in outside lever unlocks door. Clutched operation of outside lever when locked by key outside or turn-button inside.



CLUTCHED ENTRY - L253 - (ANSI F109)
Turn/pushbutton locking: pushing and turning button locks outside lever, requiring use of key until button is manually unlocked. Pushbutton locking: pushing button locks outside lever until unlocked by key or by turning inside lever. Clutched operation of outside lever when locked by key outside or turn-button inside.



ENTRY - LX253 / K253 - (ANSI F109)
Turn/pushbutton locking: pushing and turning button locks outside lever, requiring use of key until button is manually unlocked. Pushbutton locking: pushing button locks outside lever until unlocked by key or by turning inside lever.



CLUTCHED CLASSROOM - L270 / K270 - (ANSI F84)
Outside lever locked and unlocked by key. Inside lever always unlocked. Clutched operation of outside lever when locked by key outside or turn-button inside.



CLASSROOM - LX270 / K270 - (ANSI F84)
Outside lever locked and unlocked by key. Inside lever always unlocked.



CLUTCHED STOREROOM - L280 - (ANSI F86)
Outside lever fixed. Entrance by key only. Inside lever always unlocked. Clutched operation of outside lever when locked by key outside or turn-button inside.



STOREROOM - LX280 / K280 - (ANSI F86)
Outside lever fixed. Entrance by key only. Inside lever always unlocked.



DUMMY - L2170
Single trim surface mounted lever

GENERAL LOCK

Quality & Value™

— Product Guide 103.1 — Ab:1