

Grade 3 Standard Tubular Handlesets

HT Series - Applications, Features, and Functions

APPLICATIONS:

High-end residential handlesets suitable for interior and exterior doors of office buildings, hotel / motel, storefronts, multi-family housing, condominiums, and apartments.



FEATURES:

CERTIFICATIONS: ANSI A156.2, Series 4000 Grade 3

FINISHES: 605 and 626

DOOR THICKNESS: 1-3/8" - 1-3/4"

LATCH / BOLT: Fixed 2-3/8" square-corner latch standard. Fixed 2-3/4" square-corner latch optional. Bolt is adjustable 2-3/4" / 2-3/8" with square-corner face plate. Latch / Bolt face plates are 2-1/4" x 1".

STRIKE: 2-1/4" curved lip square-corner strike standard for knob portion. Square deadbolt strike for deadbolt portion.

CYLINDER: Drilled 5, pinned 5, solid brass cylinder and housing with KW1. Cylinder is rekeyable and master-keyable.

KEYS: 2 cut keys

TRIM: Standard trim is "P" knob; "T" knob, "L" lever, and "D" lever are optional

CASE QUANTITY: 6

WARRANTY: 25-year mechanical warranty and 5-year finish warranty

FUNCTIONS:



ENTRY / OFFICE - HT360

Deadbolt retracted by key from outside or by inside turn. Latch retracted by thumbpiece from outside or by inside knob.



DUMMY - KT170, LT170

Decorative trim that is non-functional

GENERAL LOCK

Quality & Value™

— Product Guide 103.1 — Ad:5